



**NOTES:**

1. TO INSPECT ASSEMBLY, FOLLOW FIRST ARTICLE AND IN PROCESS INSPECTION SHEET.
2. PUT THESE ITEMS IN SEPARATE PLASTIC BAGS.
3. TORQUE TO 8 +/-0.5 LB-FT.
4. APPLY THIN COAT OF SILICON GREASE FOR ALL O-RINGS BEFORE INSTALLATION.
5. APPLY LOCTITE 242, IF SCREW DOES NOT HAVE NYLON PATCH.
6. APPLY LOCTITE 680.
7. PULL OUT HOSE AND APPLY SILICON GREASE, BETWEEN HOUSE AND SPOUT, 10" FROM OUTLET TO HOSE.
8. TORQUE SWIVEL NUT TO 10 +/-2 LB-IN.
9. TORQUE TO 10 +/-2 LB-FT.
10. TORQUE TO 7 +/-2 LB-IN.
11. PARTIALLY THREAD MOUNTING KIT ONTO SHANK.
12. DO NOT DOCK SPRAY HEAD TO SPOUT WHEN PACKAGING.

**BILL OF MATERIAL (CURRENT LEVEL)**

ITEM	PT/ASSY	DESCRIPTION	TYPE	QTY.
1	13486	BODY, TAFT PULL-DOWN	PART	1
2	12667	SPOUT ADAPTER	PART	1
3	91030	O-RING, #2- 115, EPDM, 65-75 DURO, NSF 61	PART	4
4	91712	SLEEVE	PART	1
5	13464	ADAPTER EXTENSION	PART	1
6	91114	O-RING, #2- 116, EPDM, 65-75 DURO, NSF 61	PART	2
7	1-064	SINGLE LEVER CARTRIDGE	PART	1
8	2-781	CART. RETAINER ASM	ASSEMBLY	1
9	12823	HANDLE HUB	PART	1
10	11874	HANDLE ADAPTER SCREW	PART	1
11	91534	CARTRIDGE STEM INSERT	PART	1
12	13487	PULLDOWN SPOUT - SHORT	PART	1
13	91544	MAGNET DOCKING	ASSEMBLY	1
14	11877	HOSE, PULLDOWN SWIVEL	ASSEMBLY	1
15	3-480	SPRAY HEAD, EAST LINEAR	ASSEMBLY	1
16	20-313	HANDLE LEVER ASM	ASSEMBLY	1
17	1-457	INTEGRATED SUPPLY HOSE	ASSEMBLY	1
18	1-458	OUTLET HOSE	ASSEMBLY	1
19	13440	SHANK	PART	1
20	1-256	MOUNTING KIT	ASSEMBLY	1
21	91568	RETAINER CLIP	PART	1
22	1-286	WEIGHT ASM	ASSEMBLY	1
23	91139	WASHER RBR 1-3/8	PART	1

-	N	EN-4446	01/27/22	C.G.
-	M	EN-4213D	09/10/21	C.G.
-	L	EN-4300s	03/29/21	R.S.
-	K	EN-4273	10/13/20	V.V.
-	J	EN-4167	06/12/20	JMR
-	H	EN-4051	01/17/20	J.M.
-	G	EN-3931B	09/06/19	V.V.
-	F	EN-3539B	09/06/19	V.V.
-	E	EN-3413j	06/19/18	J.A.
-	D	EN-3413c	01/10/18	JM
-	C	EN-3034L	09/11/17	J.A
-	B	EN-3034F	04/20/17	J.A
-	A	EN-3034	04/13/17	J.A
-	-	EN-2682	03/17/14	-
ZONE	REV	DESCRIPTION	DATE	APPROVED

COPYRIGHT 2005 BRASSTECH, INC. THESE DRAWINGS AND THE DESIGNS DEPICTED HEREIN ARE THE PROPRIETARY PROPERTY OF BRASSTECH. ANY USE OR REPRODUCTION IS SUBJECT TO THE EXPRESS APPROVAL OF BRASSTECH. UNAUTHORIZED USE IS STRICTLY PROHIBITED. ALL RIGHTS RESERVED.

TESTING	-	-	-
ASSEMBLY	-	-	-
PLATING	-	-	-
POLISHING	-	NEXT ASSY	USED ON
MACHINING	-	APPLICATION	
TOOLING FIXTURE #	REMOVE ALL BURRS AND SHARP EDGES		

UNITS ARE: INCHES [MM]  
TOLERANCES ARE:  
FRACTIONS DECIMALS ANGLES  
±1/16" .X ±.1 [2,5] ±1°  
.XX ±.06 [1,5]

(X.XXX) DENOTES CRITICAL DIMS.  
ALL THREADS ARE CRITICAL

DRAWN	JINSON	01/27/22
CHECKED	C.G.	01/27/22
APPROVED	C.G.	01/27/22

**BRASSTECH** 2001 CARNEGIE AVE.  
SANTA ANA, CA 92705  
(949) 417-5207  
INCORPORATED

**EAST LINEAR PULL DOWN -  
BAR/PERP FAUCET**

DWG NO. **1500-5223** REV **N**

SCALE .150 REF. SHEET 1 OF 2

