	4	3	•	2				
	NOTES:			BILL OF MATERIAL (CURRENT LEVEL)				
	(N) I. FIT / FORM / FUNCTION SHALL FOL	LLOW PS-E.008.		ITEM PT/ASSY	DESCRIPTION	TYPE	QTY.	
				I 6-403 A.V.	1/2" CU X 3/8" CMP	ASSEMBLY	I	
D					S HANDLE	PART		D
				3 92000 SCREV	N 8 - 32 X 1/8 SS	PART	I	
		(1)						
-								
			$4 \times$					
		$ \setminus $						
								C
C								С
					NA/			
						\rightarrow		
								4
	2							
		- LA				/		
		$< \$						
В		\backslash		J.F.				В
							D	
			[]					
		[<u></u>	FR	NITS ARE: INCHES [MM] DLERANCES ARE: RACTIONS DECIMALS ANGLES	RASSTECH	2001 CARNEGIE A SANTA ANA, CA 9	VE. 2705	
A		TESTING - ASSEMBLY -	± *	$\frac{1}{16^{\circ}}$ x + 1 (2.5) $\pm 1^{\circ}$ IN	CORPORATED			А
	- E EN-430011 10/25/21 N.S. COPYRIGH		· · ·	.XX E.UG (1,3) .XXX) DENOTES CRITICAL DIMS. LL THREADS ARE CRITICAL	/2" COMP. X 3/8"	2044L	ř	
	THESE DR	RAWINGS AND THE DESIGNS D HEREIN ARE THE PROPRIETARY POLISHING		LL THREADS ARE CRITICAL RAWN NMS 10/25/21 DWG	VALVE		REV	
	- C EN-1699 02/03/11 R.S.	Y OF BRASSTECH AW USE TOLISHING - ODUCTON IS SUBJECT O RESS APPROVAL OF BRASSTECH, MACHINING - NIZED USE IS STRICTLY TED. ALL RIGHTS RESERVED. TOOLING FIXTURE #	APPLICATION	HECKED N. SANTOS 10/25/21	¹⁰ 403X		E	
	ZONE REV DESCRIPTION DATE APPROVED PROHIBIT		REMOVE ALL BURRS AND SHARP EDGES		LE .000 REF.	SHEET OF	2	
	4	3	•	2				

