

# 95GH'GE I 5F 9

## : YUhi fYg

- Solid brass construction
- Bridge-style brass valve bodies
- Quarter-turn washerless ceramic disc valve cartridges
- Swivel spout assembly
- Solid brass pull-out sidespray assembly
- 11.21" (21.2 cm) spout height at outlet
- 9.00" (22.8 cm) spout reach (c-c)
- For 8.00" (20.3 cm) centers
- ADA Complaint (Handles Only)
- 1.8 GPM (6.8 LPM) Max

6f]X[ Y`GhmY`? ]hWYb` : Ui W'hk ]h`G]XYgdfUm

%(\$\$!) (%)



## 7cXYg`#`GhUbXUfXg`7ca d`]UbW

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAMPO/cUPC
- NSF/ANSI/CAN 61, SECTION 9
- NSF/ANSI 372
- IPC
- ADA & ICC/ANSI A117.1 (Handle Only)
- Energy Policy Act of 1992
- California Energy Commission
- ASME A112.18.3 (Back Flow)
- All applicable US Federal and State material regulations



## 7c`cfg`#` : ]b]g\Yg

- 10B: Oil Rubbed Bronze
- 15: Polished Nickel
- 15S: Satin Nickel - PVD
- 26: Polished Chrome

• Other: Refer to the Newport Brass catalog for additional color/finish options.

## GdYVZ]YX`A cXY`

A cXY`	8YgW]dh]cb	7c`cfg`p` : ]b]g\Yg				
1400-5413	Bridge Style Kitchen Faucet with Sidespray	<input type="checkbox"/> 10B	<input type="checkbox"/> 15	<input type="checkbox"/> 15S	<input type="checkbox"/> 26	<input type="checkbox"/> Other

## DfcXi Vh`GdYVZ]W]h]cb 5XX`17c`cf`#` : ]b]g\`gi Z]l`hc`A cXY`bi a VYfz`VY`ck "

The Bridge Style Kitchen Faucet shall be made of solid brass construction. Faucet shall incorporate a swivel spout assembly with integral side-spray diverter assembly and feature bridge-style brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.8 gallons (6.8 liters) per minute maximum flow rate. Product shall be for 8.00" (20.3 cm) centers. Product shall incorporate a 11.21" (28.5 cm) spout height at outlet and a 9.00" (22.8 cm) spout reach (c-c). Faucet shall incorporate traditional lever handles. Bridge-Style Kitchen Faucet with Sidespray shall be Newport Brass Model 1400-5413/\_\_\_\_ .

