

ASTAIRE

Features

- Solid brass construction
- 7.43" (18.9 cm) spout length
- 3/4" NPT spout inlet fitting (1/2" NPT bushing included)
- Rough valve incorporates a brass valve body assembly
- Rough valve incorporates quarter-turn washerless ceramic disc valve cartridges
- Intended for use with Newport Brass rough valve as specified (Required Accessory)
- ADA Compliant

Wall-Mounted Tub Trim

3-1645





Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1-18
- IAMPO/cUPC
- IPC
- ADA & ICC/ANSI A117.1
- All applicable US Federal and State material regulations

Colors / Finishes • 10B: Oil Rubbed Bronze

- 15: Polished Nickel
- 15S: Satin Nickel PVD • 26: Polished Chrome



Other: Refer to the Newport Brass catalog for additional color/finish options

Specified Model			
Model	Description	Colors Finishes	
3-1645	Wall-Mounted Tub Trim	☐ 10B ☐ 15 ☐ 15S ☐ 26 ☐ Other	

Required Accessory			
Application	Wall Tub Rough Valve		
Description	2-Cartridge Assembly		
Inlet/Outlet Size	1/2"		
Part Number	1-500U		
Image			

Product Specification Add "Color / Finish" suffix to Model number, below.

The Wall-Mounted Tub Trim shall be made of solid brass construction. Wall-Mounted Tub Trim shall include cross handles and a 7.43" (18.9 cm) tub spout that incorporates a 3/4" NPT inlet fitting (adaptable to 1/2" NPT via included adapter). Wall-Mounted Tub Trim shall be Newport Brass Model 3-1645/____ and Newport Brass rough valve shall be 1-500U.

3-1645

Product dimensions are provided for reference only. For specific product installation guidelines, please reference the installation instructions of the product being installed.

