

## **GRIFFEY**

#### **Features**

- Solid brass construction
- 8.79" (22.3 cm) spout length
- 1/2" NPT spout inlet fitting
- Rough valve incorporates a brass valve body assembly
- Rough valve incorporates quarter-turn washerless ceramic disc valve cartridges
- Intended for use with Newport Brass rough valve as specified (Required Accessory)
- ADA Compliant

# Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1-18
- IAMPO/cUPC
- IPC
- ADA & ICC/ANSI A117.1
- All applicable US Federal and State material regulation

#### **Colors / Finishes**


- 10B: Oil Rubbed Bronze
  15: Polished Nickel
  15S: Satin Nickel PVD
- 26: Polished Chrome
- Other: Refer to the Newport Brass catalog for additional color/finish options.

#### **Wall-Mounted Tub Trim**

3-3285







Specified Model			
Model	Description	Colors   Finishes	
3-3285	Wall-Mounted Tub Trim	☐ 10B ☐ 15 ☐ 15S ☐ 26 ☐ Other	

Required Accessory		
Application	Wall Tub Rough Valve	
Description	2-Cartridge Assembly	
Inlet/Outlet Size	1/2"	
Part Number	1-500U	
Image		

### Product Specification Add "Color / Finish" suffix to Model number, below.

The Wall-Mounted Tub Trim shall be made of solid brass construction. Wall-Mounted Tub Trim shall include cross handles and a 8.79'' (22.3 cm) tub spout that incorporates a 1/2'' NPT inlet fitting. Wall-Mounted Tub Trim shall be Newport Brass Model  $3-3285/\_\_$  and Newport Brass rough valve shall be 1-500U.

## 3-3285

Product dimensions are provided for reference only. For specific product installation guidelines, please reference the installation instructions of the product being installed.

