

# **NADYA**

#### **Features**

# Single-Handle Kitchen Faucet with Sidespray

- Solid brass construction
- Euro-motion ceramic disc 35 mm valve cartridge
- Swivel spout assembly with top-accessible diverter
- Solid brass pull-out sidespray assembly
- 5.63" (14.3 cm) spout height at outlet
- 9.68" (24.6 cm) spout reach (c-c)
- For two hole configurations
- ADA Complaint (Handles Only)
- 1.8 GPM (6.8 LPM) Max



## **Codes / Standards Compliance**

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAMPO/cUPC
- NSF/ANSI/CAN 61, SECTION 9
- NSF/ANSI 372
- IPC
- ADA & ICC/ANSI A117.1 (Handle Only)
- Energy Policy Act of 1992
- California Energy Commission
- ASME A112.18.3 (Back Flow)
- All applicable US Federal and State material regulations



#### **Colors / Finishes**

- 10B: Oil Rubbed Bronze
  15: Polished Nickel
  15S: Satin Nickel PVD
- 26: Polished Chrome
- Other: Refer to the Newport Brass catalog for additional color/finish options.

# Specified Model Model Description Colors | Finishes 941 Single-Handle Kitchen Faucet with Sidespray 10B 15 15S 26 Other

# Product Specification Add "Color / Finish" suffix to Model number, below.

The Single-Handle Kitchen Faucet with Sidespray shall be made of solid brass construction. Faucet shall incorporate a swivel spout assembly with top-accessible side-spray diverter assembly and feature a Euro-motion ceramic disc 35 mm valve cartridge. Faucet shall have a 1.8 gallons (6.8 liters) per minute maximum flow rate. Product shall require two holes for installation. Product shall incorporate a 5.63" (14.3 cm) spout height at outlet and a 9.68" (24.6 cm) spout reach (c-c). Faucet shall incorporate a top-mounted ADA lever handle for temperature and flow control. Single-Handle Kitchen Faucet with Sidespray shall be Newport Brass Model 941/\_\_\_\_ .

# 941

### **PRODUCT DIMENSIONS** (Units are in inches)

Product Dimensions are provided for reference only. For specific product installation guidelines, please reference the Installation Instructions of the product being installed.

